



LUXMAN L-507s

INTEGRATED AMPLIFIER

LUX CORPORATION, TOKYO, JAPAN

SERIAL NO.

W71011763E



定格電圧 AC 100V
定格周波数 50/60Hz
定格消費電力 240W

BALANCED

RIGHT

PHASE

- 1 GROUND
- 2 COLD (-)
- 3 HOT (+)

normal
 reverse





INPUT SELECTOR

CD
tuner
line-1
line-2
bal. line
tape-1
tape-2
phono
phono MC

VOLUME CONTROL
-dB

18
16
14
12
10
8
6
5
3
2
1
0
30
38
50
63
75
∞



POWER

phones

REC SELECTOR

tuner off CD

line-1 tape-1

line-2 tape-2

bal. line phono

SPEAKERS

off A B A+B

MODE SELECTOR

left ch. stereo right ch. mono

TONE CONTROL

bass treble

BALANCE

center

line straight subsonic loudness

INTEGRATED AMPLIFIER ULTIMATE L-3076







CAUTION
RISK OF ELECTRIC SHOCK
DO NOT OPEN

ATTENTION
RISQUE DE CHOC ELECTRIQUE
NE PAS OUVRIR

SIGNAL GROUND

PHONO LEFT RIGHT
CD
TUNER
LINE-1
LINE-2

TAPE-1 REC OUT MONITOR
TAPE-2 REC OUT MONITOR
PRE OUT MAIN IN LEFT RIGHT

LUXMAN L-507s
INTEGRATED AMPLIFIER
LUX CORPORATION, TOKYO, JAPAN

SERIAL NO.
W71011763E

定額電圧 AC 100V
定額周波数 50/60Hz
定額消費電力 240W

BALANCED CD

RIGHT PHASE LEFT

1 GROUND
2 COLD(-)
3 HOT(+)

□ normal
△ reverse

BALANCED LINE

RIGHT PHASE LEFT

1 GROUND
2 COLD(-)
3 HOT(+)

□ normal
△ reverse

SPEAKERS

SPEAKERS A

RIGHT LEFT

SPEAKERS B

LOAD A+B 4

LUXMAN CS
735118

BUS LINE

LINE PHASE SENSOR

UNSWITCHED (TOTAL 300W max.)

AC IN

MADE IN JAPAN