
naim
naim audio
prev
next
stop
play


naim


naim




AC ONLY
FREQUENCY: 50/60Hz
INPUT POWER: 25VA
FUSE RATINGS: 100V TO 120V: T2A
200V TO 240V: T1A. 250V.
N1501
CONFORMS TO EN 60065.
DESIGNED AND MADE IN ENGLAND BY NAIM AUDIO LTD.
SOUTHAMPTON ROAD SALISBURY.
PLEASE READ MANUAL BEFORE USE
TYPE: FLATCAP 2
SERIAL No.
OFF
ON
230V
WARNING:
THIS APPARATUS MUST BE EARTHED
WARNING:
DISCONNECT SUPPLY CORD BEFORE OPENING
ATTENTION:
DEBRANCHER AVANT D'OUVRIR
REFER TO MANUAL
POWER OUT A
SIGNAL OUT A
SIGNAL OUT B
SIGNAL OUT C
+24V 0.2A
+24V 0.2A
ch2
ch1
-ve
unused
REFER TO MANUAL
POWER OUT B
SIGNAL OUT D
+22V 0.1A
A.C. ONLY~
230V
FUSE RATING:
100 TO 120V: T2A.
200 TO 240V: T1A.250V.
POWER
WARNING: DISCONNECT SUPPLY CORD BEFORE OPENING.
ATTENTION: DEBRANCHER AVANT D'OUVRIR.
FREQ: 50/60 HZ. I/P POWER: 25 V.A.
CONFORMS TO BS EN 60065 : 1994
DESIGNED AND MADE IN ENGLAND BY NAIM AUDIO LTD. SOUTHAMPTON RD. SALISBURY.
TYPE: NACD3-5.
CLASS 1 LASER PRODUCT
TO BS7192
disc
DIGITAL AUDIO
Link
AUX P/S
ch.1
ch.2